



REV	DESCRIPTION	DATE	BY
1	INITIAL		
2	INCREASED LAYR. OF FLEE COND. ADDED. CLIP ON FACE OF DRL. CLIP IN BINA ATNG. WAS 1/8. CHANGED TYPE OF CLIP USED. CHG. B/M.		
3	REMOVED 2 CONDUT CLIPS. CHG. B/M. 2000AC-8		
4	ADDED 2000AC-8		
5	ADDED 2000AC-8		
6	ADDED 2000AC-8		
7	ADDED 2000AC-8		
8	ADDED 2000AC-8		
9	ADDED 2000AC-8		
10	ADDED 2000AC-8		
11	ADDED 2000AC-8		
12	ADDED 2000AC-8		
13	ADDED 2000AC-8		
14	ADDED 2000AC-8		
15	ADDED 2000AC-8		
16	ADDED 2000AC-8		
17	ADDED 2000AC-8		
18	ADDED 2000AC-8		
19	ADDED 2000AC-8		
20	ADDED 2000AC-8		

E.O. 22861
 20-16228
 BROWDER III
 E.D.C. 3-25-41
 P.D.V. 5





VIEW C-C
SCALE 12" = 1 FT




VIEW B
SCALE 12" = 1 FT




- 2000AC-8 (6)
- AN 931-T-11 (7) REF
- AN 931-T-11 (7) REF
- AN 931-T-11 (7) REF
- AN 931-T-11 (7) REF
- AN 931-T-11 (7) REF



FERRULE & COUPLING NUT SHOULD BE INSTALLED AFTER CONDUIT IS IN SHIP



DRILL #20 (140) 4 HOLES
 CUT 1" DIA HOLE
 HOLES TO MATCH 20E1245



VIEW A-A
SCALE 12" = 1 FT

NAF 213021-2-100 (1)
 NAF 213021-2 (1)
 NAF 213021-3 (2)
 NOTE: TAPE HIGH SPOTS OF NAF 213021-2-100 THAT LOOP AWAY FROM SKIN. TAPE FLEX WHERE MEMBERS ARE CROSSED

PARTS MARKED 9 ARE 6 FT.
 THIS ONE COVERS CHANGE #40 ON PBY-1

NOTE: DRILL & DRILL HOLE IN LOWEST POINT OF CONDUIT BOX (WHEN SHIP IS ON BEACHING CRAN)

INSTALLATION AT PILOT'S SWITCH PANEL
 FOR PBY-1 ONLY
 SCALE 12" = 1 FT

H 230

REV	DESCRIPTION	DATE	BY
1	INITIAL		
2	INCREASED LAYR. OF FLEE COND. ADDED. CLIP ON FACE OF DRL. CLIP IN BINA ATNG. WAS 1/8. CHANGED TYPE OF CLIP USED. CHG. B/M.		
3	REMOVED 2 CONDUT CLIPS. CHG. B/M. 2000AC-8		
4	ADDED 2000AC-8		
5	ADDED 2000AC-8		
6	ADDED 2000AC-8		
7	ADDED 2000AC-8		
8	ADDED 2000AC-8		
9	ADDED 2000AC-8		
10	ADDED 2000AC-8		
11	ADDED 2000AC-8		
12	ADDED 2000AC-8		
13	ADDED 2000AC-8		
14	ADDED 2000AC-8		
15	ADDED 2000AC-8		
16	ADDED 2000AC-8		
17	ADDED 2000AC-8		
18	ADDED 2000AC-8		
19	ADDED 2000AC-8		
20	ADDED 2000AC-8		